



C79860 Nickel Silver Alloy Wire

Fisk Alloy Wire Inc.
P.O. Box 26
10 Thomas Road N.
Hawthorne, NJ 07506 U.S.A.

Phone: (973) 825-8500
Fax: (973) 427-4585
E-mail: sales@fiskalloy.com

©2025 Fisk Alloy Wire Inc.
Percon is a registered
trademark of Fisk Alloy
Wire Inc.
Information provided on
this page is for reference
purposes only.

C79860 Nickel Silver Alloy Wire

Chemical Composition - Limits	Chemical Composition - Nominal
-------------------------------	--------------------------------

Fabrication Index	
Soldering	
Hot Worked	
Cold Worked	
Brazing	
Machinability	

Physical Properties

Annealing Range (Min)	50 °F
Annealing Range (Max)	60 °F
Electrical Resistivity (Annealed)	207.4 Ω ·cir-mil/ft @ 68 °F
Electrical Conductivity (Annealed)	5% IACS @ 68 °F
Melting Point (Solidus)	1,620 °F
Melting Point (Liquidus)	1,880 °F

C79860 Nickel Silver Alloy Wire

Fisk Alloy Wire Inc.
P.O. Box 26
10 Thomas Road N.
Hawthorne, NJ 07506 U.S.A.

Phone: (973) 825-8500
Fax: (973) 427-4585
E-mail: sales@fiskalloy.com

©2025 Fisk Alloy Wire Inc.
Percon is a registered
trademark of Fisk Alloy
Wire Inc.
Information provided on
this page is for reference
purposes only.